Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-018-1432

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

## **Terminal Length:**

1.500 inches

## **Body Diameter:**

0.375 inches

#### **Body Length:**

1.625 inches

## **Terminal Diameter:**

0.032 inches

## Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## **Electrical Polarization:**

Polarized

## **Capacitance Value Per Section:**

12.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

## **Case Material:**

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

10.0000

Dc Leakage At Reference Temp:

5.000 microamperes

## **Case Insulation Material:**

Plastic or rubber

## **Test Data Document:**

81349-mil-c-39018/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

Unit Of Measure:

# NSN 5910-01-018-1432

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0