NSN 5910-01-018-3906

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-018-3906

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Body Length:
0.420 inches
Body Width:
0.330 inches
Body Height:
0.160 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
10000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section
50.0 dc single section
50.0 dc single section Tolerance Range Per Section:
50.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section
50.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material:
50.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic
50.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
50.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads
50.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Terminal Surface Treatment:
50.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Terminal Surface Treatment: Solder
50.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Terminal Surface Treatment: Solder Terminal Type And Quantity:
50.0 dc single section Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Tolerance Range Per Section: -1.00/+1.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: