

View Online at <https://aerobasegroup.com/nsn/5910-01-018-6969>

Body Style:

Rotary

Terminal Length:

0.359 inches

Body Diameter:

0.531 inches

Body Height:

0.234 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Center To Center Distance Between Terminals Parallel To Diameter:

0.390 inches

Quality Factor At 25 Deg Celsius:

500.0

Inclosure Type:

Encased

Adjustment Device Torque:

Between 2.000 inch-ounces and 8.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10.0 gigohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+3.0/+12.0 single section

Nonderated Voltage Rating And Type:

350.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-4.50/+2.00 single section and -2.50/+2.00 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.50 single section

Material:

Ceramic inclosure

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0