## NSN 5910-01-019-1240

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-019-1240

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
45.0 millimeters
Body Length:
26.5 millimeters
Body Width:
5.0 millimeters
Body Height:
17.0 millimeters
Terminal Diameter:
0.8 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.680 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 100.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 250.0 dc single section
250.0 dc single section
250.0 dc single section  Tolerance Range Per Section:
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material:
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material:  Metal
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp:
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material:  Metal  Insulation Resistance At Reference Temp: 20000.0 megohms
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Metal Insulation Resistance At Reference Temp: 20000.0 megohms  Terminal Surface Treatment:
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Metal Insulation Resistance At Reference Temp: 20000.0 megohms  Terminal Surface Treatment: Solder
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Metal Insulation Resistance At Reference Temp: 20000.0 megohms  Terminal Surface Treatment: Solder  Terminal Type And Quantity:
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Metal Insulation Resistance At Reference Temp: 20000.0 megohms  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Metal Insulation Resistance At Reference Temp: 20000.0 megohms  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Metal Insulation Resistance At Reference Temp: 20000.0 megohms  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Metal Insulation Resistance At Reference Temp: 20000.0 megohms  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Metal Insulation Resistance At Reference Temp: 20000.0 megohms  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a Unit Of Measure:
250.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Metal Insulation Resistance At Reference Temp: 20000.0 megohms  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: