

View Online at <https://aerobasegroup.com/nsn/5910-01-020-3253>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Established

Terminal Length:

Between 0.625 inches and 0.875 inches

Body Diameter:

0.225 inches

Body Length:

0.425 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.095 inches and 0.155 inches

Schematic Diagram Designator:

Two terminals common to one electrode

Anode Type:

Solid

Electrical Polarization:

Polarized

Capacitance Value Per Section:

4.700 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

20.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

6.0000

Dc Leakage At Reference Temp:

2.000 microamperes

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0