NSN 5910-01-020-5682

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-020-5682

•
Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
0.390 inches
Body Diameter:
0.216 inches
Body Length:
0.360 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.100 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Impedance At Minimum Operating Tempurature In Ohms:
2.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
10.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
25.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
Dissipation Factor At Reference Tempurature In Percent: 8.000
8.000
8.000 Dc Leakage At Reference Temp:
8.000 Dc Leakage At Reference Temp: 4.000 microamperes

2 uninsulated wire lead

NSN 5910-01-020-5682

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0