NSN 5910-01-020-7149

Body Style:

Specification Data:

81349-mil-c-19978/2b government specification

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-020-7149

W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 2.000 inches **Body Diameter:** 0.531 inches **Body Length:** 1.562 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 0.015 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 2000.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Ceramic or glass **Insulation Resistance At Reference Temp:** 25000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 1.000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Paper and plastic polyethylene terephthalate **Test Data Document:** 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead

NSN 5910-01-020-7149

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| Shelf Life: |
|------------------|
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

Fiig:

A010b0