NSN 5910-01-020-7152

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-020-7152

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Length:
0.175 inches
Body Width:
0.120 inches
Body Height:
0.135 inches
Terminal Diameter:
0.010 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Electrical Polarization:
Nonpolarized
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius
Between -55.0 degrees celsius and 85.0 degrees celsius
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 0.500 microamperes
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 0.500 microamperes Terminal Surface Treatment:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 0.500 microamperes Terminal Surface Treatment: Solder
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 0.500 microamperes Terminal Surface Treatment: Solder Terminal Type And Quantity:
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: 6.0000 Dc Leakage At Reference Temp: 0.500 microamperes Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead

--

NSN 5910-01-020-7152

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0