NSN 5910-01-020-9411

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-020-9411

Rody	Style:
Douv	Style.

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

Reliability Indicator:

Not establishednot established

Terminal Length:

1.313 inches 1.313 inches

Body Diameter:

0.875 inches

Body Length:

0.300 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.690 inches and 0.810 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

1000.000 picofarads single section

Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-33.0/+22.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

10000.0 dc single section

Tolerance Range Per Section:

-20.00/+80.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

3.0000

Terminal Surface Treatment:

Solder

Special Features:

Special burn-in test

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5910-01-020-9411

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demi			

No

Fiig:

A010b0