NSN 5910-01-021-5308

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-021-5308

| Body Style: |
|---|
| W/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite |
| surfaces |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 1.250 inches |
| Body Length: |
| 0.875 inches |
| Body Width: |
| 0.150 inches |
| Body Height: |
| 0.380 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 196.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -65.0 degrees celsius and 95.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 ac-rms single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -30.0/+30.0 single section |
| Tolerance Range Per Section: |
| -1.00/+1.00 percent single section |
| Case Material: |
| Plastic |
| Power Factor At Reference Tempurature In Percent: |
| 0.4000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 5910-01-021-5308

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0