

View Online at <https://aerobasegroup.com/nsn/5910-01-022-3074>

Body Style:

W/o mtg facilities, terminal (s) on one surface

Mil-std-1276 Wire Lead Type Designator:

C

Reliability Indicator:

Not established

Unable To Decode:

Unable to decode and unable to decode

Terminal Length:

1.500 inches

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Body Length:

Between 0.485 inches and 0.515 inches

Body Width:

Between 0.185 inches and 0.265 inches

Body Height:

Between 0.485 inches and 0.515 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.375 inches and 0.425 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.075 inches and 0.150 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Section Quantity:

2

Capacitance Value Per Section:

10000.000 picofarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 all sections

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc all sections

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 all sections

Tolerance Range Per Section:

-2.00/+2.00 percent all sections

Case Material:

Plastic

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.1500

Terminal Type And Quantity:

4 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0