

View Online at <https://aerobasegroup.com/nsn/5910-01-022-3074>

**Body Style:**

W/o mtg facilities, terminal (s) on one surface

**Mil-std-1276 Wire Lead Type Designator:**

C

**Reliability Indicator:**

Not established

**Unable To Decode:**

Unable to decode and unable to decode

**Terminal Length:**

1.500 inches

**Unable To Decode:**

Unable to decode and unable to decode

**Unable To Decode:**

Unable to decode and unable to decode

**Body Length:**

Between 0.485 inches and 0.515 inches

**Body Width:**

Between 0.185 inches and 0.265 inches

**Body Height:**

Between 0.485 inches and 0.515 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.375 inches and 0.425 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.075 inches and 0.150 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Section Quantity:**

2

**Capacitance Value Per Section:**

10000.000 picofarads all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

0.0 all sections

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc all sections

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-30.0/+30.0 all sections

**Tolerance Range Per Section:**

-2.00/+2.00 percent all sections

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

10000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.1500

**Terminal Type And Quantity:**

4 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0