# NSN 5910-01-023-2452

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-023-2452

# **Body Style:**

W/o mtg facilities, terminal (s) on one end

## **Reliability Indicator:**

Not established

# **Terminal Length:**

1.500 inches

## **Body Diameter:**

0.250 inches

### **Body Length:**

0.500 inches

## Center To Center Distance Between Terminals Parallel To Diameter:

0.125 inches

### **Terminal Diameter:**

0.025 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

## Anode Type:

Solid

## **Electrical Polarization:**

Polarized

# **Capacitance Value Per Section:**

68.000 microfarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Dc Leakage At Maximum Operating Temp:

10.0 microamperes

# Nonderated Continuous Voltage Rating And Type Per Section:

6.0 dc single section

# **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### Case Material:

Plastic

# **Capacitive Electrode Material:**

Tantalum

# **Dissipation Factor At Reference Tempurature In Percent:**

10.0000

# Dc Leakage At Reference Temp:

1.000 microamperes

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

# NSN 5910-01-023-2452

Electrolytic Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0