NSN 5910-01-023-2456

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-023-2456

, , , , , , , , , , , , , , , , , , ,
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
Between 1.625 inches and 1.725 inches
Body Diameter:
0.415 inches
Body Length:
0.945 inches
Continuous Current Rating In Amps:
1.0
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
4.700 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
500.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.5000
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5910-01-023-2456

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	atio	

No

Fiig:

A010b0