

View Online at <https://aerobasegroup.com/nsn/5910-01-023-5383>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.750 inches

Body Diameter:

0.580 inches

Body Length:

1.570 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j; los angeles class ssn (688); helicopter, advance attack, ah-1w; helicopter, mh-53e; helicopter, carrier based asw, sh-60f; support equipment, b-52 aircraft; virginia class cgn (41); ticonderoga class cg (47); austin ship class lpd-4 amphibious transport docks

Insulation Resistance At Maximum Operating Temp:

5000.0 megohms

Capacitance Value Per Section:

0.010 microfarads single section

Nonderated Operating Temp:

Between -35.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

6000.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

50000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0