

View Online at <https://aerobasegroup.com/nsn/5910-01-023-5383>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

1.750 inches

**Body Diameter:**

0.580 inches

**Body Length:**

1.570 inches

**Terminal Diameter:**

0.032 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

Helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j; los angeles class ssn (688); helicopter, advance attack, ah-1w; helicopter, mh-53e; helicopter, carrier based asw, sh-60f; support equipment, b-52 aircraft; virginia class cgn (41); ticonderoga class cg (47); austin ship class lpd-4 amphibious transport docks

**Insulation Resistance At Maximum Operating Temp:**

5000.0 megohms

**Capacitance Value Per Section:**

0.010 microfarads single section

**Nonderated Operating Temp:**

Between -35.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

6000.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

50000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

1.0000

**Terminal Surface Treatment:**

Solder

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0