Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-023-5385

## Body Style:

W/o mtg facilities, axial terminals

# Mil-std-1276 Wire Lead Type Designator:

N-2

**Reliability Indicator:** 

Not established

#### **Terminal Length:**

1.625 inches

#### **Body Diameter:**

0.690 inches

**Body Length:** 

1.375 inches

#### **Terminal Diameter:**

0.032 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

25000.0 megohm-microfarads

## Capacitance Value Per Section:

1.000 microfarads single section

### Nonderated Operating Temp:

Between -62.0 degrees celsius and 125.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

500000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.0300

# Case Insulation Material:

Plastic

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

### Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0