# NSN 5910-01-024-0820

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-024-0820

#### **Body Style:**

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

#### **Reliability Indicator:**

Not establishednot established

#### **Terminal Length:**

1.250 inches 1.250 inches 1.250 inches

#### **Body Diameter:**

0.280 inches

### **Body Length:**

0.120 inches

#### **Center To Center Distance Between Terminals Parallel To Diameter:**

0.250 inches

# **Terminal Diameter:**

0.025 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

#### **Insulation Resistance At Maximum Operating Temp:**

1000.0 megohms

# **Capacitance Value Per Section:**

3.000 picofarads single section

# **Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

# Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

#### **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:**

-120.0/+120.0 single section

#### **Tolerance Range Per Section:**

-0.25/+0.25 picofarads single section

#### **Case Material:**

Plastic

#### **Insulation Resistance At Reference Temp:**

500000.0 megohms

# **Dissipation Factor At Reference Tempurature In Percent:**

0.1500

#### **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

# Shelf Life:

N/a

# NSN 5910-01-024-0820

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0