NSN 5910-01-024-3318

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-024-3318 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 25.0 millimeters **Body Diameter:** 16.0 millimeters **Body Length:** 25.0 millimeters **Center To Center Distance Between Terminals Parallel To Diameter:** 7.5 millimeters **Terminal Diameter:** 0.8 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 2.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 220.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -10.00/+30.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent: Equivalent Series Resistance At Reference Tempurature In Ohms:** 0.525 Dc Leakage At Reference Temp:

4.000 microamperes **Terminal Surface Treatment:** Solder

NSN 5910-01-024-3318

Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0