

View Online at https://aerobasegroup.com/nsn/5910-01-024-9571

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.1000

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.374 inches

**Body Length:** 

0.874 inches

**Terminal Diameter:** 

0.032 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### **Capacitance Value Per Section:**

0.220 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

**Terminal Surface Treatment:** 

Solder

# **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

**Specification Data:** 

81349-mil-c-39022/1 government specification

Shelf Life:

N/a



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0