NSN 5910-01-025-0801

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-025-0801

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
2.500 inches
Body Length:
1.740 inches
Body Width:
0.550 inches
Body Height:
0.750 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
2.300 microfarads single section
Nonderated Operating Temp:
Between -65.0 degrees celsius and 80.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section
400.0 dc single section
400.0 dc single section Tolerance Range Per Section:
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material:
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms Terminal Surface Treatment:
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms Terminal Surface Treatment: Solder
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity:
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
400.0 dc single section Tolerance Range Per Section: -0.00/+100.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 200.0 megohms Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: