## NSN 5910-01-026-2178

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-026-2178

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

#### **Reliability Indicator:**

Not establishednot established

### **Terminal Length:**

1.250 inches 1.250 inches 1.250 inches

#### **Body Diameter:**

0.920 inches

#### **Body Length:**

0.218 inches

#### **Center To Center Distance Between Terminals Parallel To Diameter:**

0.375 inches

## **Terminal Diameter:**

0.032 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

### **Insulation Resistance At Maximum Operating Temp:**

10000.0 megohms

### **Capacitance Value Per Section:**

6800.000 picofarads single section

## **Voltage Tempurature Limits Per Section In Percent Capacitance Change:**

-82.0/+22.0 without voltage applied single section

#### **Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

350.0 ac-rms single section and 3000.0 dc single section

## **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

50000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

3.000

#### **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5910-01-026-2178

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0