

View Online at https://aerobasegroup.com/nsn/5910-01-026-5980

Body Style:
Rotary
Body Length:
0.750 inches
Body Width:
0.531 inches
Body Height:
0.234 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Quality Factor At 25 Deg Celsius:
400.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.312 inches
Inclosure Type:
Encased
Adjustment Device Torque:
Between 2.000 inch-ounces and 8.000 inch-ounces
Insulation Dc Resistance At 25 Deg Celsius:
10.0 gigohms
Mounting Facility Type And Quantity:
2 unthreaded hole
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Capacitance Range In Picofarads:
+10.0/+75.0 single section
Nonderated Voltage Rating And Type:
350.0 dc continuous single section
Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius:
+6.00/+16.00 single section and -11.00/-6.00 single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.50 single section
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5910-01-026-5980

Ceramic Dielectric Variable Capacitor - Page 2 of 2

Fiig: A096a0

