NSN 5910-01-026-6315

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-026-6315
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
0.207 inches
Body Length:
0.750 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
5000.0 megohms
Capacitance Value Per Section:
0.001 microfarads single section
Nonderated Operating Temp:
Between -65.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.1500
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polycarbonate
Case Insulation Material:
Plastic
Test Data Document:
91240 mil a 10079 aposification (includes anginogring type bulleting, breehurgs, etc., that reflect aposification type data in aposification

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-01-026-6315

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Fiig: A010b0