## NSN 5910-01-026-6316

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-026-6316

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.450 inches
Body Width:
0.160 inches
Body Height:
0.290 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
200.0 megohms
Capacitance Value Per Section:
0.015 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp:
Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms
Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:
Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.3000
Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.3000  Terminal Surface Treatment:
Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.3000  Terminal Surface Treatment: Solder
Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.3000  Terminal Surface Treatment: Solder  Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.3000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead
Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.3000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
Nonderated Continuous Voltage Rating And Type Per Section:  100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.3000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a

No

## NSN 5910-01-026-6316

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0