Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-027-2011

## Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

## **Terminal Length:**

1.000 inches

#### **Body Length:**

1.040 inches

#### **Body Width:**

0.560 inches

#### **Body Height:**

0.400 inches

## Center To Center Distance Between Terminals Parallel To Length:

0.800 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **End Application:**

Instrument landing system (ilstype2)

#### Capacitance Value Per Section:

1.000 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

100000.0 megohm-microfarads

# Dissipation Factor At Reference Tempurature In Percent:

0.5000

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A010b0