

View Online at https://aerobasegroup.com/nsn/5910-01-027-5800

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

## **Reliability Indicator:**

Established

# **Terminal Length:**

1.250 inches

## **Body Length:**

0.190 inches

#### **Body Width:**

0.190 inches

### **Body Height:**

## 0.090 inches

## Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

### **Terminal Diameter:**

0.025 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Capacitance Value Per Section:

22.000 picofarads single section

# Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

100000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

2.5000

## Test Data Document:

81349-mil-c-39014/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

## Shelf Life:

N/a



Demilitarization:

No

Fiig:

A010b0