NSN 5910-01-027-9496

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-027-9496

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.748 inches
Body Width:
0.512 inches
Body Height:
0.295 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.022 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
No. 1. or 10
Nonderated Continuous Voltage Rating And Type Per Section:
250.0 ac-rms single section
250.0 ac-rms single section
250.0 ac-rms single section Tolerance Range Per Section:
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material:
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment:
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Terminal Type And Quantity:
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
250.0 ac-rms single section Tolerance Range Per Section: -20.00/+20.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: