

View Online at https://aerobasegroup.com/nsn/5910-01-028-0198

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.625 inches

Body Diameter:

0.562 inches

Body Length:

1.875 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Internal Electrical Connection Type:

Extended foil

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

Capacitance Value Per Section:

0.180 microfarads single section

Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

25000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Dielectric Material:

Paper and plastic polyethylene terephthalate

Case Insulation Material:

Plastic

Test Data Document:

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-19978/19a government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0