NSN 5910-01-028-2484

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-028-2484

Body Style:
W/o mtg facilities, axial terminals
Mil-std-1276 Wire Lead Type Designator:
N-2
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
0.255 inches
Body Length:
0.687 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
250000.0 megohms
Capacitance Value Per Section:
0.002 microfarads single section
Nonderated Operating Temp:
Between -62.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-0.025/+0.025 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
5000000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.0300
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5910-01-028-2484

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0