NSN 5910-01-029-0731

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-029-0731

Body Style:

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

Between 7.875 inches and 8.062 inches

Body Width:

Between 7.875 inches and 8.062 inches

Body Height:

Between 5.875 inches and 6.062 inches

Center To Center Distance Between Terminals Parallel To Length:

3.438 inches

Terminal Diameter:

0.190 inches

Terminal Height From Body:

2.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

6.000 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

6.000 inches

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

8 threaded mounting studs

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

3.500 microfarads single section

Nonderated Operating Temp:

Between 0.0 degrees celsius and 75.0 degrees celsius

Thread Size:

0.250 inches

Nonderated Continuous Voltage Rating And Type Per Section:

11000.0 dc single section

Tolerance Range Per Section:

+0.0/+10.0 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

6000.0 megohm-microfarads

No Fiig: A010b0

NSN 5910-01-029-0731
Plastic Dielectric Fixed Capacitor - Page 2 of 2



Dissipation Factor At Reference Tempurature in Percent:	
1.0000	
Terminal Type And Quantity:	
2 standoff, threaded stud	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	