

View Online at <https://aerobasegroup.com/nsn/5910-01-029-1554>

Body Style:

W/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfaces

Reliability Indicator:

Not establishednot establishednot establishednot established

Terminal Length:

0.250 inches 0.250 inches 0.250 inches 0.250 inches

Body Length:

0.135 inches 0.135 inches

Body Width:

Between 0.065 inches and 0.065 inches and 0.100 inches 0.100 inches

Body Height:

0.110 inches 0.110 inches

Schematic Diagram Designator:

No common or grounded electrode (s)no common or grounded electrode(s)

Insulation Resistance At Maximum Operating Temp:

100000.0 megohms100000.0 megohms

Capacitance Value Per Section:

12.000 picofarads single section12.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and -55.0 degrees celsius and 125.0 degrees celsius 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

90.0 single section90.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section200.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section-20.0/+20.0 single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section-5.00/+5.00 percent single section

Case Material:

Ceramicceramic

Insulation Resistance At Reference Temp:

1000000.0 megohms1000000.0 megohms

Quality Factor At Reference Temp:

6667.0006667.000

Precious Material And Location:

Terminals silverterminals silver

Terminal Type And Quantity:

2 ribbon

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0