NSN 5910-01-029-1556

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-029-1556

Body	Stv	le:
DOUN	/ ULV	IC.

W/o mtg facilities, terminals on opposite surfacesw/o mtg facilities, terminals on opposite surfaces

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

0.250 inches

Body Length:

0.127 inches

Body Width:

0.100 inches

Body Height:

0.110 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

18.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

90.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

100000.0 megohms

Quality Factor At Reference Temp:

4444.000

Terminal Surface Treatment:

Silver

Precious Material And Location:

Terminal surfaces silver

Terminal Type And Quantity:

2 ribbon

Shelf Life:

N/a

Unit Of Measure:

__

NSN 5910-01-029-1556

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0