Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-029-1787

## **Body Style:**

W/o mtg facilities, terminals on opposite surfaces

### **Reliability Indicator:**

Not established

## Terminal Length:

1.375 inches

### **Body Length:**

0.290 inches

### **Body Width:**

0.110 inches

**Body Height:** 

0.220 inches

### **Terminal Diameter:**

0.016 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Electrical Polarization:**

Polarized

## **Capacitance Value Per Section:**

8.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Dc Leakage At Maximum Operating Temp:

20.0 microamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

### **Tolerance Range Per Section:**

-0.00/+4.00 microfarads single section

### **Case Material:**

Plastic

### **Capacitive Electrode Material:**

Tantalum

## **Dissipation Factor At Reference Tempurature In Percent:**

6.0000

### Dc Leakage At Reference Temp:

2.000 microamperes

## **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 uninsulated wire lead

### Shelf Life:

N/a

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0