

View Online at <https://aerobasegroup.com/nsn/5910-01-029-6382>

**Body Style:**

W/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:**

Established/established/established

**Reliability Failure Rate Level In Percent:**

2.00002.00002.0000

**Width Across Flats:**

0.187 inches 0.187 inches 0.187 inches

**Terminal Length:**

0.365 inches 0.365 inches 0.365 inches

**Body Length:**

0.359 inches

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Insulation Resistance At Maximum Operating Temp:**

10000.0 megohms

**Capacitance Value Per Section:**

1500.000 picofarads single section

**Voltage Temperature Limits Per Section In Percent Capacitance Change:**

-66.0/+22.0 with rated voltage applied single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.164 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section

**Tolerance Range Per Section:**

-20.00/+80.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

3.0000

**Test Data Document:**

81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

1 solder stud and 1 uninsulated wire lead

**Specification Data:**

81349-mil-c-39014/18 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0