Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-030-1410

## Body Style:

W/o mtg facilities terminal (s) on one surface

## **Reliability Indicator:**

Not established

## **Terminal Length:**

1.250 inches

#### **Body Length:**

0.550 inches

#### **Body Width:**

Between 0.455 inches and 0.475 inches

### **Body Height:**

0.250 inches

## Center To Center Distance Between Terminals Parallel To Length:

0.400 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

### Capacitance Value Per Section:

0.022 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### Case Material:

Metal

# Insulation Resistance At Reference Temp:

60000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.3000

# Terminal Type And Quantity:

2 uninsulated wire lead

# Shelf Life:

N/a

# Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0