NSN 5910-01-030-1788

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5010-01-030-1788

view Online at https://aerobasegroup.com/nsi//5910-01-050-1766
Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.000 inches
Body Length:
0.430 inches
Body Width:
0.300 inches
Body Height:
0.851 inches
Center To Center Distance Between Terminals Parallel To Length
0.350 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
500.0 megohm-microfarads
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-2.00/+2.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
50000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.5000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a

Unit Of Measure:

NSN 5910-01-030-1788

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



			on:	

No

Fiig:

A010b0