## NSN 5910-01-030-3353

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-030-3353	
Body Style:	
W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals	
Reliability Indicator:	
Not establishednot established	
Terminal Length:	
1.000 inches 1.000 inches	
Body Diameter:	
0.100 inches	
Body Length:	
0.170 inches	
Terminal Diameter:	
0.016 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Capacitance Value Per Section:	
1.000 picofarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsiu	ıs:
0.0 single section	
Nonderated Continuous Voltage Rating And Type Per Section:	
50.0 dc single section	
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:	
-30.0/+30.0 single section	
Tolerance Range Per Section:	
-5.00/+5.00 percent single section	
-5.00/+5.00 percent single section  Case Material:	
Case Material:	
Case Material: Plastic	
Case Material: Plastic Insulation Resistance At Reference Temp:	
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms	
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp:	
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 150.0000	
Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Quality Factor At Reference Temp:  150.0000  Terminal Surface Treatment:	
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 150.0000 Terminal Surface Treatment: Solder	
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 150.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity:	
Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Quality Factor At Reference Temp:  150.0000  Terminal Surface Treatment:  Solder  Terminal Type And Quantity:  2 uninsulated wire lead	
Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Quality Factor At Reference Temp:  150.0000  Terminal Surface Treatment:  Solder  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:	

No

Demilitarization:

## NSN 5910-01-030-3353

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0