## NSN 5910-01-030-7655

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



radial terminals

View Online at https://aerobasegroup.com/nsn/5910-01-030-7655

Body Style:
W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities,
Reliability Indicator:
Not establishednot established
Terminal Length:
1.250 inches 1.250 inches 1.250 inches
Body Diameter:
0.125 inches
Body Length:
0.320 inches
Center To Center Distance Between Terminals Parallel To Length:
0.250 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
15.800 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
50000.0 megohms
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5910-01-030-7655

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0