## NSN 5910-01-031-4854

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-031-4854

<b>D</b> -	٠. د	C4	٠
DU	uv	Stv	ıe:

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s)

## **Reliability Indicator:**

Not establishednot established

**Terminal Length:** 

1.500 inches 1.500 inches 1.500 inches

**Body Length:** 

0.200 inches

**Body Width:** 

0.200 inches

**Body Height:** 

0.100 inches

Center To Center Distance Between Terminals Parallel To Length:

0.100 inches

**Terminal Diameter:** 

0.016 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

270.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-3300.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-650.0/+650.0 single section

**Tolerance Range Per Section:** 

-2.00/+2.00 percent single section

**Case Material:** 

Plastic

**Insulation Resistance At Reference Temp:** 

2500.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1000

**Quality Factor At Reference Temp:** 

1000.0000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-031-4854

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		fe:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0