NSN 5910-01-032-1653

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-032-1653
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Terminal Length:
1.500 inches
Body Diameter:
0.219 inches
Body Length:
0.484 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
5.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
3.4000
Dc Leakage At Reference Temp:
1.000 microamperes
Case Insulation Material:
Plastic
Test Data Document:
81349-mil-c-3900619 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-01-032-1653

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0