NSN 5910-01-032-4168

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-032-4168

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

Reliability Indicator:

Not establishednot established

Terminal Length:

1.698 inches 1.698 inches 1.698 inches

Body Diameter:

0.258 inches

Body Length:

0.106 inches

Center To Center Distance Between Terminals Parallel To Length:

0.250 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.204 inches

Terminal Diameter:

0.024 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

200.000 picofarads single section

Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-7.5/+7.5 without voltage applied single section

Nonderated Operating Temp:

Between 10.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

7500.0 megohms

Power Factor At Reference Tempurature In Percent:

1.5000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5910-01-032-4168

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0