View Online at https://aerobasegroup.com/nsn/5910-01-033-7203

Plastic Dielectric Fixed Capacitor - Page 1 of 2

Body Style:

W/thd bushing mtg, terminals on opposite ends

Reliability Indicator:

Not established

Terminal Length:

0.200 inches

Body Diameter:

0.562 inches

Body Length:

1.375 inches

Continuous Current Rating In Amps:

10.0

Unf

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

0.470 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.312 inches

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0