## NSN 5910-01-033-7883

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-033-7883

D.	~~	١.,	Stv	. 1	۸.
0	υu	IV	SIV	41	e:

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s)

## **Reliability Indicator:**

Not establishednot established

**Terminal Length:** 

1.500 inches

**Body Length:** 

0.200 inches

**Body Width:** 

0.200 inches

**Body Height:** 

0.125 inches

Center To Center Distance Between Terminals Parallel To Length:

0.100 inches

**Terminal Diameter:** 

0.020 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

460.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 150.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** 

-30.0/+30.0 single section

**Tolerance Range Per Section:** 

-1.00/+1.00 percent single section

**Case Material:** 

Plastic

**Insulation Resistance At Reference Temp:** 

2500.0 megohms

**Quality Factor At Reference Temp:** 

1000.0000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-033-7883

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0