NSN 5910-01-034-1784

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-034-1784 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Body Length:** 0.420 inches **Body Width:** 0.300 inches **Body Height:** 0.180 inches Center To Center Distance Between Terminals Parallel To Length: 0.300 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 25.0 megohm-microfarads **Capacitance Value Per Section:** 0.100 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 25000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.3000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

Unit Of Measure:

NSN 5910-01-034-1784

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	2 †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0