## NSN 5910-01-034-2590

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-034-2590

view Offilite at https://aerobasegroup.com/nsn/55/10-01-054-2550
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Terminal Length:
2.250 inches
Body Diameter:
0.406 inches
Body Length:
0.921 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
560.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
6.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
128.0000
Dc Leakage At Reference Temp:
2.000 microamperes
Case Insulation Material:
Plastic
Test Data Document:
81349-mil-c-39006/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-034-2590

Electrolytic Fixed Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A010b0