

View Online at <https://aerobasegroup.com/nsn/5910-01-035-0375>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.0001

Terminal Length:

0.343 inches

Body Length:

3.250 inches

Body Width:

1.000 inches

Body Height:

1.062 inches

Center To Center Distance Between Terminals Parallel To Length:

0.500 inches

Center To Center Distance Between Terminals Parallel To Width:

0.500 inches

Unthreaded Mounting Hole Diameter:

0.169 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.625 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Mounting Facility Type And Quantity:

4 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

75.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

1200.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.2500

Power Factor At Reference Temperature In Percent:

2.0000

Test Data Document:

98230-0n230645 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0