

View Online at <https://aerobasegroup.com/nsn/5910-01-035-0375>

**Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.0001

**Terminal Length:**

0.343 inches

**Body Length:**

3.250 inches

**Body Width:**

1.000 inches

**Body Height:**

1.062 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.500 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.500 inches

**Unthreaded Mounting Hole Diameter:**

0.169 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.625 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.625 inches

**Mounting Facility Type And Quantity:**

4 unthreaded mounting holes

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

75.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

1200.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:**

0.2500

**Power Factor At Reference Tempurature In Percent:**

2.0000

**Test Data Document:**

98230-0n230645 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0