## NSN 5910-01-035-1524

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-035-1524

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Length:
0.220 inches
Body Width:
0.290 inches
Body Height:
0.110 inches
Center To Center Distance Between Terminals Parallel To Length:
0.180 inches
Terminal Diameter:
0.016 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Electrical Polarization:
Polarized
Capacitance Value Per Section:
10.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
30.0 microamperes
ocio illionosi il porto
Nonderated Continuous Voltage Rating And Type Per Section:
•
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section
Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material:
Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic
Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Capacitive Electrode Material:
Nonderated Continuous Voltage Rating And Type Per Section:  20.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Capacitive Electrode Material: Tantalum
Nonderated Continuous Voltage Rating And Type Per Section:  20.0 dc single section  Tolerance Range Per Section: -20.00/+20.00 percent single section  Case Material: Plastic  Capacitive Electrode Material:  Tantalum  Dissipation Factor At Reference Tempurature In Percent:

Solder

**Terminal Surface Treatment:** 

## NSN 5910-01-035-1524

Electrolytic Fixed Capacitor - Page 2 of 2



Ferminal Type And Quai	ntity	:
------------------------	-------	---

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0