Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-035-4714

### Body Style:

W/o mtg facilities terminal (s) on one surface

#### **Reliability Indicator:**

Established

### Reliability Failure Rate Level In Percent:

1.0000

### **Terminal Length:**

1.000 inches

#### **Body Length:**

0.500 inches

#### Body Width:

0.280 inches

### Body Height:

0.125 inches

### Center To Center Distance Between Terminals Parallel To Length:

# 0.400 inches

**Terminal Diameter:** 

0.020 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

3300.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

### Case Material:

Plastic

### Insulation Resistance At Reference Temp:

1000000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.2500

# Test Data Document:

81349-mil-c-55514/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

2 uninsulated wire lead

#### Shelf Life:

N/a

Unit Of Measure:

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0